



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 1 of 27

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

WAXILIT 22-71F

UFI: ENNU-D8X1-Y5R2-Q2AY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Lubricant

Uses advised against

Consumer uses: Private households (= general public = consumers)

Sector of uses [SU]: 21

Do not use for private purposes (household).

Relevant identified uses - Further information:

Industrial uses: Uses of substances as such or in preparations at industrial sites

Sector of uses [SU]: 3

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Sector of uses [SU]: 22

The product is intended for professional use.

1.3. Details of the supplier of the safety data sheet

Manufacturer

Company name: ACMOS CHEMIE KG

Street: Industriestrasse 49

Place: D-28199 Bremen

Post-office box: 10 10 69

D-28010 Bremen

Telephone: +49 (0)421-5189-0

Telefax: +49 (0)421-511415

e-mail: acmos@acmos.com

Contact person: Mr. Stephan Dryhaus

e-mail: sds@acmos.comInternet: www.acmos.com

Responsible Department: Laboratory (Division: Occupational- / Product security) - see under section 16

1.4. Emergency telephone number:

+44 111 (Emergency information service / official advisory body: National Poisons

Information Service - NPIS Birmingham) (<https://www.npis.org>)

Language(s) of Telephone Service: EN

Supplier

Company name: ACMOS CHEMIE KG

Street: Industriestrasse 49

Place: D-28199 Bremen

Post-office box: 10 10 69

D-28010 Bremen

Telephone: +49 (0)421-5189-0

Telefax: +49 (0)421-511415

e-mail: acmos@acmos.com

Contact person: Mr. Stephan Dryhaus

e-mail: sds@acmos.comInternet: www.acmos.com

Responsible Department: Laboratory (Division: Occupational- / Product security) - see under section 16

1.4. Emergency telephone number:

+44 111 (Emergency information service / official advisory body: National Poisons

Information Service - NPIS Birmingham) (<https://www.npis.org>)

Language(s) of Telephone Service: EN

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 2 of 27

Flam. Liq. 3; H226
Asp. Tox. 1; H304
STOT SE 3; H336
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements

GB CLP Regulation

Hazard components for labelling

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics
hydrocarbons, C9, aromatics

Signal word: Danger

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P370+P378 In case of fire: Use Water mist/Extinguishing powder/Foam/Carbon dioxide (CO2) to extinguish.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

Additional advice on labelling

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

2.3. Other hazards



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 3 of 27

Adverse physicochemical effects:

See section 9 for physical and chemical properties.

The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration.

The accumulation in lowlying or closed rooms can cause increased danger of fire and explosion.

Vapours can travel considerable distances to a source of ignition where they can ignite, flash back, or explode.

Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment.

Therefore keep away from fire and sources of ignition.

This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

This material can accumulate static charge by flow or agitation and can be ignited by static discharge.

The product will be applied by spraying.

In use may form flammable/explosive vapour-air mixture.

Even after use and until complete evaporation of the flammable components, there is still a danger of an explosive steam-air mixture forming.

Adverse human health effects and symptoms:

See section 11 for toxicological information.

Adverse environmental effects:

See section 12 for environmental information.

Other adverse effects:

Special danger of slipping by leaking/spilling product.

Results of PBT-/vPvB-assessment:

See under section 12.5 - Results of PBT and vPvB assessment.

Endocrine disrupting properties:

See under section 11.2 + 12.6 - Endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Active ingredients in a mixture of solvents

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-49-0	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	65 - < 70 %		
	927-241-2		01-2119471843-32	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412 EUH066			
64742-95-6	hydrocarbons, C9, aromatics	10 - < 15 %		
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
64742-49-0	927-241-2	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	65 - < 70 %	
	inhalation: LC50 = > 5,6 mg/l (dusts or mists); dermal: LD50 = > 5000 mg/kg; oral: LD50 = > 5000 mg/kg			
64742-95-6	918-668-5	hydrocarbons, C9, aromatics	10 - < 15 %	
	inhalation: LC50 = > 10,2 mg/l (vapours); dermal: LD50 = > 3160 mg/kg; oral: LD50 = 3492 mg/kg			



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 4 of 27

Further Information

The above mentioned EC-No. (Provisional List Number 9xx-xxx-x) is a specific subset of the specified CAS-No. and was associated with the registration process automatically (without CAS-No. or numeric identifier). An official announcement by the EC inventory will follow after evaluation of substance identity by the ECHA. The new nomenclature of hydrocarbon solvents is only related with group names of the HSPA (Hydrocarbon Solvents Producers Association). The previously used CAS-No. continues serving as a reference for different global inventories. The classification of hydrocarbon mixtures made in consideration of the applicable notes in annex VI of regulation (EC) No. 1272/2008.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down.
Take off immediately all contaminated clothing and wash it before reuse.
Put victim at rest, cover with a blanket and keep warm.
Do not leave affected person unattended.
If a person vomits when lying on his back, place him in the recovery position.
If breathing is irregular or stopped, administer artificial respiration.
If unconscious but breathing normally, place in recovery position and seek medical advice.
Never give anything by mouth to an unconscious person or a person with cramps.
In the event of cardiac arrest immediately perform cardiopulmonary resuscitation.
In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Self-protection of the first aider:

Wear personal protection equipment (refer to section 8).

First Aid.

Notes for the doctor:

Aspiration hazard

Risk of product entering the lungs on vomiting after ingestion.

Aspiration may cause pulmonary oedema and pneumonitis.

Symptoms may develop several hours following exposure; medical observation therefore necessary for at least 48 hours.

After inhalation

Remove victim out of the danger area.

Provide fresh air.

In the case of lung irritation: Primary treatment using corticoide spray, eg. Auxiloson spray, Pulmicort-dosage-spray. (Auxiloson and Pulmicort are registered trademarks.) Call a physician immediately.

Consult a doctor immediately in the case of inhaling spray mist and show him packing or label.

After contact with skin

Wash immediately with:

Water and soap

Rub greasy ointment into the skin.

Do not wash with:

Solvents/Thinner

In case of skin irritation, consult a physician.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

If present: Initial treatment with Previn. (Previn is a registered trademark).

Protect uninjured eye.

After ingestion

Do NOT induce vomiting.

Give nothing to eat or drink.

Observe risk of aspiration if vomiting occurs.

Never give anything by mouth to an unconscious person or a person with cramps.

Call a physician immediately.



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 5 of 27

4.2. Most important symptoms and effects, both acute and delayed

The following symptoms may occur:

Cough
Dyspnoea
Cyanosis (blue coloured blood)
Pulmonary oedema
Pneumonia
Depression of central nervous system
Headache
Nausea
Dizziness
Dizziness
Inebriation
Unconsciousness

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

In case of ingestion, the stomach should be emptied by gastric lavage under qualified medical supervision.

Regulation of the blood circulation, possible shock treatment.

Where appropriate artificial ventilation.

Subsequent observance for pneumonia and lung oedema.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water mist
Extinguishing powder (ABC-powder)
Foam
Carbon dioxide (CO₂)

Fire class (EN 2): B (Fires of liquids or liquid turning substances)

Unsuitable extinguishing media

Full water jet
Water spray jet

5.2. Special hazards arising from the substance or mixture

In principle, fire gasses of organic materials have to be classified as toxic to the respiratory system.

Burning produces heavy smoke.

Hazardous combustion products:

Carbon monoxide
carbon dioxide (CO₂)
Hydrocarbons
Pyrolysis products, toxic

5.3. Advice for firefighters

Usual measures of preventive and averting fire protection.

Co-ordinate fire-fighting measures to the fire surroundings.

Do not inhale explosion and combustion gases.

Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.

Beware of reignition.

Use caution when applying carbon dioxide in confined spaces. Carbon dioxide can displace oxygen.

Move undamaged containers from immediate hazard area if it can be done safely.

Stop and contain spill/release if it can be done safely. If this cannot be done, allow fire to burn under control.

Use water spray jet to protect personnel and to cool endangered containers.

Closed containers may burst when pressure and temperature rise

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 6 of 27

DIN-/EN-Norms EN 469

Firefighting protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

- Avoid contact with skin, eyes and clothes.
- Do not breathe vapour/aerosol.
- Remove all sources of ignition.
- Prevent further leakage or spillage if safe to do so.
- Remove persons to safety.
- Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.
- Provide adequate ventilation.
- Special danger of slipping by leaking/spilling product.

For non-emergency personnel

- Use personal protection equipment.
- Walk out of the danger zone and notify trained personnel.
- Emergency procedures: Keep the factory emergency plan and the information chain.

For emergency responders

- Use personal protection equipment.
- The personal protective equipment must be adapted to the situation.
- Suitable material:
- See under section 8.2 - Personal protection equipment.

6.2. Environmental precautions

- Do not allow to enter into surface water or drains.
- Do not allow to enter into soil/subsoil.
- Ensure waste is collected and contained.
- Suppress gases/vapours/mists with water spray jet.
- In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment

- Repair leaks if without risk.
- Move containers from spill area.
- Make sure spills can be contained, e.g. in sump pallets or kerbed areas.
- Prevent spread over a wide area (e.g. by containment or oil barriers).
- Remove from the water surface (e.g. skimming, sucking).
- Cover drains.

For cleaning up

- Large amounts of spillages:
 - Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).
 - Shovel into suitable container for disposal.
 - Local authorities should be advised if significant spillages cannot be contained.

Small amounts of spillages:

- Clear spills immediately.
- Wipe up with absorbent material (eg. cloth, fleece).
- Collect in closed and suitable containers for disposal.
- Clear contaminated areas thoroughly.
- Recommended cleansing agent:
 - Clean with detergents. Avoid solvent cleaners.
 - Retain contaminated washing water and dispose it.
 - Ensure all waste water is collected and treated via a waste water treatment plant.
- Ventilate affected area.

Other information

- Suitable material for taking up:
 - Sand
 - Kieselguhr



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 7 of 27

Universal binder
Absorbing material, organic

Unsuitable material for taking up:
None known

6.4. Reference to other sections

Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Measures to prevent aerosol and dust generation:
All work processes must always be designed so that the following is as low as possible:
Inhalation of vapours or spray/mists
Eye contact
Skin contact

Technical ventilation of workplace
Vapours are heavier than air.
Provide room air exhaust at ground level.
During filling, metering and sampling should be used if possible:
Splashproof grounded devices
Devices with local exhaust
Use only in a exhaust booth with integrated air filter.
Use in ventilated spray booths only.
Recirculation of exhaust air is not recommended.
Always close containers tightly after the removal of product.

Advice on protection against fire and explosion

Measures to prevent fire:
The product is: Flammable
The formation of combustible vapours is possible at temperatures above: +10 °C (Flash point - 15 °C)
Vapours can form explosive mixtures with air.
Spray mist may be flammable at temperatures below the flash point.
Reignition possible over considerable distance.
Vapours are heavier than air, spread along floors and form explosive mixtures with air.
Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.
Provide earthing of containers, equipment, pumps and ventilation facilities.
Use explosion-proof machinery, apparatus, ventilation facilities, tools etc.
Use non-sparking tools.
Take precautionary measures against static discharges.
Flammable vapours can accumulate in head space of closed systems.
Only use the material in places where open light, fire and other flammable sources can be kept away.
Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.
Usual measures for fire prevention.
Fire-fighting equipment on the basis of class B.
Never use pressure to empty container.
Wear anti-static footwear and clothing

Measures according to German "Explosion rules" required:
Prevention measures regarding formation of explosible atmosphere (restriction and supervision of concentration, inertisation, airtightness, ventilation, warning device, etc.).
Prevention measures regarding ignition of explosible atmosphere (zone graduation, removing of ignition sources, explosion-proof electrical installation, earthing, etc.).
Constructive measures for restriction of effects regarding explosions (resistance to pressure of explosions, discharge of pressure of explosions, suppression of explosions, etc.).

Advice on general occupational hygiene

Advices on general occupational hygiene:



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 8 of 27

Wear personal protection equipment (refer to section 8).
Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.
General industrial hygiene practice.
Handle in accordance with good industrial hygiene and safety practice.
Working places should be designed to allow cleaning at any time.
Floors, walls and other surfaces in the hazard area must be cleaned regularly.
Clean spray booth and exhaust hood completely with every product change.
When using do not eat, drink, smoke, sniff.
Thorough skin-cleansing after handling the product.
Used working clothes should not be worn outside the work area.

Further information on handling

Environmental precautions:
Shafts and sewers must be protected from entry of the product.
Transfer wash-downs in sealed containers.
Provide for retaining containers, e.g. floor pan without outflow.
For restriction of emission on volatile organic compounds (VOC) the solvent vapours should be supplied to an exhaust air purification facility (filter, gas washer, incineration).

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Suitable floor material:
Floors should be impervious, resistant to liquids and easy to clean.

Protect against:
Heat
Cold

Recommended storage temperature: +10 ... +30 °C

Keep away from:
Food and feedingstuffs

Packaging materials:
Suitable container/equipment material:
Keep/Store only in original container.
Unsuitable container/equipment material:
See under section 8.2 - Hand protection.

Hints on joint storage

Do not store together with:
Storage class:
1 (Explosive hazardous substances)
2 A (Gases (except aerosol dispensers and lighters))
4.1 A (Other potentially explosive hazardous substances)
4.1 B (flammable solids)
4.2 A (Pyrophoric or self-heating substances)
4.3 (Hazardous substances that release flammable gases when in contact with water)
5.1 A (Highly oxidising substances)
5.1 C (Ammonium nitrate and preparations containing ammonium nitrate)
5.2 (Organic peroxides and self-reactive substances)
6.1 B (Non-combustible substances of acute toxicity, category 1 and 2 / very toxic substances)
6.2 (Infectious substances)
7 (Radioactive substances)

Further information on storage conditions

Technical measures and storage conditions:
The valid water and zoning ordinances must be observed.
Heating causes rise in pressure with risk of bursting.
Keep away from sources of ignition - No smoking.
Keep in a cool, well-ventilated place.
Keep container tightly closed.



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 9 of 27

Protect containers against damage.
Ensure adequate ventilation of the storage area.
Store small packages in a suitable, robust cabinet.
Do not store outside.
See also instructions on the label.

7.3. Specific end use(s)

Recommendation:
Possibilities for substitution and references to less hazardous products:
This product was designed for a special application purpose and optimized appropriately.
In case of questions regarding product and application, please contact our field service in line with customer service or our technical sales department.
Observe technical data sheet.

Industrial sector specific solutions:

Hazardous substance information systems of professional associations:

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
-	Aromatics	-	500		TWA (8 h)	WEL
-	Cycloalkanes >= C7	-	800		TWA (8 h)	WEL
-	Normal and branched chain alkanes >= C7 (it excludes n-heptane)	-	1200		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
64742-49-0	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics			
Worker DNEL, long-term		inhalation	systemic	871 mg/m ³
Worker DNEL, long-term		dermal	systemic	77 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	185 mg/m ³
Consumer DNEL, long-term		dermal	systemic	46 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	46 mg/kg bw/day
64742-95-6	hydrocarbons, C9, aromatics			
Worker DNEL, long-term		inhalation	systemic	150 mg/m ³
Worker DNEL, long-term		dermal	systemic	25 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	32 mg/m ³
Consumer DNEL, long-term		dermal	systemic	11 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	11 mg/kg bw/day

Additional advice on limit values

GESTIS - International Limit Values - Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung (IFA):
<http://limitvalue.ifa.dguv.de>
Country information (EU)
(<http://www.dguv.de/ifa/fachinfos/occupational-exposure-limit-values/foreign-and-eu-limit-values/index.jsp>)
Country information (GB) (<http://www.hse.gov.uk/pubns/books/eh40.htm>)
Occupational Exposure Limits of EU-memberstates - European Agency for Safety and Health at Work (OSHA)
(<http://osha.europa.eu/en/topics/ds/oel/index.stm/members.stm>)
Source of law: EH40 (GB) (<http://www.hse.gov.uk>)

Recommended monitoring procedures:
Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical

Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 10 of 27

and biological agents (BS EN 14042):

Personal air monitoring
 Room air monitoring
 Test tube
 Gas warning system
 Biological monitoring

Preliminary concentration measurements:

Suitable detector tubes for measuring the current concentration in the air at the workplace: DRÄGER test tubes - short-term tubes (<http://www.gasmesstechnik.de>)

DRÄGER test tubes - Short-term tubes - Petroleum hydrocarbons 10 / a (n-octane, measuring range: 10 - 300 ppm, response time: 60 sec) (<http://www.gasmesstechnik.de>)

DRÄGER test tubes - Short-term tubes - Petroleum hydrocarbons 100 / a (n-octane, measuring range: 100 - 2500 ppm, response time: 30 sec) (<http://www.gasmesstechnik.de>)

Exposure limits at intended use:

DNEL-/PNEC-values:

There are no exposure scenarios attached in the Appendix of this Safety Data Sheet.

Risk management measures according to used control banding approach:

Control banding for chemicals according to the ILO CHEMICAL CONTROL TOOLKIT (ICCT): ICCT-Guidelines and Control Guidance Sheets (http://www.ilo.org/legacy/english/protection/safework/ctrl_banding/toolkit/main_guide.pdf)

Used model:

Consider appropriate model solutions according to good engineering practices on designing the working process, if available.

8.2. Exposure controls



Appropriate engineering controls

Substance/mixture related measures to prevent exposure during identified uses:

Technical measures to prevent exposure:

Design of appropriate work processes and engineering controls and the use of adequate materials (physical cut-off of man and machine, model solutions as certified working methods, working appliance according to the state of the art, optimization of process / spray robots, working appliance for prevention of skin contact, models of working times).

Organisational measures to prevent exposure:

Execution of collective protection measures at source and appropriate organisational measures (local exhaust ventilation, ventilation by technical means, general ventilation, measures on averting a danger at breakdowns / at emergencies / after accidents, first-aid-measures, manner related measures: operating instruction / instruction of employees, occupational medicine health precaution).

Structural measures to prevent exposure:

Execution of individual and personnel protection measures (personal protective equipment - PPE).

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Technical measures and the application of suitable work processes have priority over personal protection equipment.

References for design of technical equipment:

See under section 7.1 - Precautions for safe handling.



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 11 of 27

Summary of the risk management measures for exposure scenario:

Use only the following product amount per time unit:

No information available.

Minimum room-width and room-height for handling/application:

No information available.

Minimum room ventilation rate for handling/application (air changes per hour):

No information available.

Individual protection measures, such as personal protective equipment

Eye/face protection

If required according to hazard assessment:

Suitable eye protection:

Eye glasses with side protection (EN 166)

Recommended eye protection articles:

UVEX I-VO / UVEX I-3 / UVEX SUPER OTG

Or comparable articles from other companies.

Hand protection

Skin protection:

Preventive skin protection.:

Draw up skin protection programme.

Before starting work, apply solvent-resistant skincare preparations.

e.g. sansibal® / sansibon®, dualin® (PETER GREVEN PHYSIODERM)

Wash hands before breaks and after work.

e.g. ecosan®, topscrub® soft / topscrub® extra / topscrub® nature (PETER GREVEN PHYSIODERM)

After cleaning apply high-fat content skin care cream.

e.g. physioderm® creme, cura soft® / cUrea soft® (PETER GREVEN PHYSIODERM)

Apply skin care products after work.

If required according to hazard assessment:

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Decrease wearing protection gloves to an inevitable degree to avoid skin rash.

Technical and organizational protective actions have to be preferred.

Breakthrough times and swelling properties of the material must be taken into consideration.

Check leak tightness/impermeability prior to use.

Wear cotton undermitten if possible.

Change preventive gloves once by hour or use special skin-protective preparations for protective gloves carrier,

e.g. physioderm® proGlove (PETER GREVEN PHYSIODERM)

Take recovery periods for skin regeneration.

Do not wear gloves near rotary machines and tools.

Dispose preventive gloves after defect or expiry of wearing time. Replace when worn.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

Wearing time with permanent contact:

Suitable gloves type

Gloves with long cuffs

Recommended glove articles:

Suitable materials at long term, direct contact (Recommended: Preventive index 6, accordingly > 480 min. permeation time in accordance to EN 374):

Fluorine rubber / FKM / Viton (KCL-VITJECT® - Art. No. 890) - Layer thickness: 0,7 mm

Or comparable articles from other companies.

Unsuitable material:

NBR (Nitrile rubber)

Butyl caoutchouc (butyl rubber)

NR (natural rubber, Natural latex)



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 12 of 27

Wearing time with occasional contact (splashes):

Suitable gloves type

Disposable gloves

Recommended glove articles:

Suitable materials at short term contact or splash (Recommended: Preventive index A, accordingly > 1-5 min.

permeation time in accordance to EN 374):

Disposable gloves of special nitrile rubber / NBR (KCL-DERMATRIL® P - Art. No. 743) - Layer thickness: 0,2 mm

Or comparable articles from other companies.

The statements are based on self-tests, literary reference and information of glove manufacturers or have been derived from similar substances by analogy.

Source: CHEMIKALIEN-MANAGER - KCL software for hand protection.

It has to be noticed, that daily time of use of chemical protective gloves may be quite shorter in practice because of many factors of influence (e.g. thermal and mechanical stress as well as special conditions on the floor) than the permeation time determined in accordance to EN 374.

The respective permeation time doubles/halves at about 1,5 times larger/lower layer thickness.

Declared permeation times according to EN 374 are not carried out under practical conditions. Therefore a maximum wearing time up to 50 % of breakthrough time is recommended.

They relate to the pure solvent as mean component.

Barrier creams are not substitutes for body protection.

Skin protection

If required according to hazard assessment:

Suitable protective clothing:

Overall, Natural fibres (e.g. cotton) (EN 340)

For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn.

DIN-/EN-Norms EN 468

Chemical protection clothing (Disposable suit antistatic)

type 6 limited splash-tight

type 5 particle-tight (method B)

type 4 spray-tight

Recommended protective clothing articles:

TYVEK CLASSIC PLUS (DU PONT)

Or comparable articles from other companies.

Chemical resistant safety shoes with conductible sole (EN ISO 20345)

Wash contaminated clothing prior to re-use.

Used working clothes should not be worn outside the work area.

Street clothing should be stored separately from work clothing.

Respiratory protection

If required according to hazard assessment:

Respiratory protection necessary at:

aerosol or mist formation + exceeding exposure limit values +

high concentrations / prolonged exposure / insufficient ventilation / insufficient exhaust

Use only respiratory protection equipment with CE-symbol including four digit test number.

Filter types: A, B, E, K. Class 1: Maximum permitted contaminant concentration in inhaled air = 1000 mL/m³ (0.1 % by vol.); class 2: maximum permitted contaminant concentration in inhaled air = 5000 mL/m³ (0.5 % by vol.); class 3:

maximum permitted contaminant concentration in inhaled air = 10000 mL/m³ (1.0 % by vol.)

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

The use of filter equipment requires a minimum oxygen content of 17 Vol-% in the surrounding atmosphere and that the



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 13 of 27

maximum permitted gas concentration - normally 0,5 Vol-% - is not exceeded.

Suitable respiratory protection apparatus:

Half-face mask or quarter facepiece: maximum use concentration for substances with exposure limits: P1 filter: up to a max. of 4 times the exposure limit. P2 filter: up to a max. of 10 times the exposure limit. P3 filter: up to a max. of 30 times the expo.

Recommended respiratory protection articles:

Half mask or quarter mask with combination filter A1P1/A2P2 for gases, vapors and particles. (EN 140, EN 14387)

Filtering half mask or quarter mask with combination filter FFA1 P1/FFA2P2 for gases, vapors and particles. (EN 405)

Gas filtrating Half-face mask FFA (EN 405)

Model 4251 (FFA1P1 - 1000 ml/m3) / 4255 (FFA2P2SL - 5000 ml/m3) (3M)

Half-face mask or Quarter-face mask with gas filter (EN 140, EN 14387)

Filter type 6051 (A1 - 1000 ml/m3) / 6055 (A2 - 5000 ml/m3) (3M)

Full-face mask with gas filter (EN 136, EN 14387)

Gas filter type: A, Indication colour: brown

Or comparable articles from other companies.

Thermal hazards

No thermal hazards during use of this product.

Environmental exposure controls

Environmental exposure controls:

Technical measures to prevent exposure:

Discharge exhaust air only with suitable separators to atmosphere.

Organisational measures to prevent exposure:

Should not be released into the environment.

Structural measures to prevent exposure:

Use the following recovery and/or abatement technique for cleaning waste gases:

Exhaust air scrubber

Adsorption

Incineration

Further information see under section 6.2 - Environmental precautions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	light yellow
Odour:	characteristic
Odour threshold:	No data available

	Test method
Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	> 140 °C literature value
Flammability	
Solid/Liquid:	The product is: Flammable
Lower explosion limits:	0,6 vol. % literature value
Upper explosion limits:	7,0 vol. % literature value
Flash point:	> 24 °C EN ISO 13736
Auto-ignition temperature:	> 200 °C literature value
Decomposition temperature:	Thermally stable.
pH-Value:	not applicable
Viscosity / kinematic: (at 40 °C)	1,5 mm ² /s DIN 53015
Water solubility: (at 20 °C)	practically insoluble: < 0,1 g/L literature value
Solubility in other solvents	
Fat solubility:	No data available



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 14 of 27

Dissolution rate:	(Nanoform) not relevant
Partition coefficient n-octanol/water:	not applicable (Mixtures)
Dispersion stability:	(Nanoform) not relevant
Vapour pressure: (at 20 °C)	< 11 hPa literature value
Vapour pressure: (at 50 °C)	< 44 hPa literature value
Density (at 20 °C):	0,8 g/cm ³ DIN 51757
Relative density:	not determined
Bulk density:	not applicable (Liquid)
Relative vapour density: (at 25 °C)	~ 4.0 (Air=1) literature value
Particle characteristics:	not applicable (Liquid)

9.2. Other information

Explosive properties

In use may form flammable/explosive vapour-air mixture.

Spray mist may be flammable at temperatures below the flash point.

The statements for steam pressure, ignition point and explosion levels apply to the solvent / solvent mixture.

Self-ignition temperature

Solid:

Not pyrophoric.

Gas:

Not pyrophoric.

Other safety characteristics

Evaporation rate: (at 20 °C)	< 0.6 (n-Butyl acetate=1) ASTM D 3539
Solvent separation test:	not applicable
Solvent content:	not determined
Solid content:	not determined
Sublimation point:	not applicable
Softening point:	not applicable
Pour point:	not applicable
Viscosity / dynamic:	not determined
Flow time: (at 23 °C)	23 s 3 DIN EN ISO 2431

Further Information

Other safety characteristics:

Mechanical sensitivity: No ignition, explosion, self-heating or visible decomposition.

miscibility: miscible with most organic solvents

Conductivity (ASTM D 2624): > 1000 pS/m

Corrosiveness: not applicable

Redox potential: not determined

radical formation potential: not applicable

photocatalytic properties: not applicable

Surface tension: not determined

Molecular weight: ~ 126 g/mol (calculated)

Temperature Class (EN 60079-0): T 3 (T > +200 °C ... <= +300 °C)

Limiting oxygen concentration (LOC) (EN 14756): No data available

Explosion group: IIA

Maximum experimental safe gap (MESG) (IEC 60079-1-1): > 0,9 mm

Minimum ignition current (MIC) (IEC 60079-11): No data available

Minimum ignition energy (MIE) (EN 13673-1): No data available

Data apply to the main component.

Data relevant with regard to physical hazard classes (supplemental):



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 15 of 27

Explosives
not applicable

Flammable gases
not applicable (Liquid)

Aerosols
not applicable (Liquid)

Oxidising gas
Not oxidising. / not applicable (Liquid)

Gases under pressure
not applicable (Liquid)

Flammable liquids
Flammable
In use may form flammable/explosive vapour-air mixture.

flammable solids
not applicable (Liquid)

Self-reactive substances and mixtures
not applicable

Pyrophoric liquids
Not pyrophoric.

Pyrophoric solids
Not pyrophoric. / not applicable (Liquid)

self-heating substances and mixtures
not applicable

Substances or mixtures which, in contact with water, emit flammable gases
not applicable

Oxidising liquids
Not oxidising.

Oxidising solids
Not oxidising. / not applicable (Liquid)

Organic peroxides
not applicable

Corrosive to metals.
Not corrosive to metals.

Desensitised explosives
not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is chemically stable under recommended conditions of storage, use and temperature.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Heat, flames and sparks.

Further information see under section 7.2 - Conditions for safe storage, including any incompatibilities.

Further information see under section 10.5 - Incompatible materials.

10.5. Incompatible materials

Violent reaction with:

Oxidising agent, strong

Further information see under section 7.1 - Precautions for safe handling.

10.6. Hazardous decomposition products

Does not decompose when used for intended uses.

No known hazardous decomposition products.

Under fire conditions: See under section 5.2 - Special hazards arising from the substance or mixture.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 16 of 27

Toxicokinetics, metabolism and distribution

There are no data available on the preparation/mixture itself.
The product has not been tested.

Information on likely routes of exposure /

Symptoms related to the physical, chemical and toxicological characteristics:

See under section 4.2 - Most important symptoms and effects, both acute and delayed.

Exposure route:

In case of ingestion:

Ingestion causes nausea, weakness and central nervous system effects.

Aspiration hazard

The risk of aspiration (penetration of liquids through the oral or nasal cavity into the trachea and lower respiratory system) is restricted solely to accidental ingestion (accident involvement) and not to the inhalation of fine mist (aerosols), as this does not result in juxtaposition of the particles, which could trigger a chemical pneumonia in the lungs.

According to the "qualitative exposure assessment" for as Asp. Tox 1, H304 classified substances and mixtures (without DNEL's) the risk management measures restricting the use of the safety P301+P310 and P331 in the SDS and on the label.

In case of skin contact:

slightly irritant but not relevant for classification.

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

In case of inhalation:

slightly irritant but not relevant for classification.

Narcotic effects

In case of eye contact:

slightly irritant but not relevant for classification.

Conjunctival redness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure:

Inhalative specific target organ toxicity (single exposure)

Interactive effects:

Not relevant

Absence of specific data:

No data is available on the product itself. Description of possible hazardous to health effects is based on experience and/or toxicological characteristics of several components.

However, some data are not complete regarding particular main components. Nevertheless according to the experience of the manufacturer there are no other hazards expected than those which are already mentioned on the label.

Mixture versus substance information:

Not relevant

Acute toxicity

Based on available data, the classification criteria are not met.



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 17 of 27

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-49-0	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 > 5000 mg/kg	Rat	ECHA	OECD 401
	dermal	LD50 > 5000 mg/kg	Rat	ECHA	OECD 402
	inhalation (4 h) dust/mist	LC50 > 5,6 mg/l	Rat	ECHA	OECD 403
64742-95-6	hydrocarbons, C9, aromatics				
	oral	LD50 3492 mg/kg	Rat [female]	ECHA	
	dermal	LD50 > 3160 mg/kg	Rabbit	ECHA	OECD 402
	inhalation (4 h) vapour	LC50 > 10,2 mg/l	Rat	ECHA	OECD 403

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

May be fatal if swallowed and enters airways.

Information on likely routes of exposure

oral: +

Dermal: +

inhalation: +

Eye contact: +

11.2. Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1. Toxicity

Aquatic toxicity:

Acute (short-term) fish toxicity:

There are no data available on the preparation/mixture itself. The product has not been tested.

Acute (short-term) toxicity to crustacea:

There are no data available on the preparation/mixture itself. The product has not been tested.

Acute (short-term) toxicity to algae and cyanobacteria:

There are no data available on the preparation/mixture itself. The product has not been tested.

Chronic (long-term) toxicity to aquatic invertebrate:

There are no data available on the preparation/mixture itself. The product has not been tested.

Chronic (long-term) fish toxicity:

There are no data available on the preparation/mixture itself. The product has not been tested.

Toxicity to other aquatic plants/organisms:

No data available (Substances/Ingredient)

Terrestrial toxicity:

Acute and subchronic bird toxicity:



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 18 of 27

No data available (Substances/Ingredient)

Bird reproduction toxicity:

No data available (Substances/Ingredient)

Acute earthworm toxicity:

No data available (Substances/Ingredient)

Chronic earthworm toxicity (reproduction):

No data available (Substances/Ingredient)

Useful insect toxicity:

No data available (Substances/Ingredient)

Acute plant toxicity:

No data available (Substances/Ingredient)

Chronic plant toxicity:

No data available (Substances/Ingredient)

Toxicity to soil macroorganisms except of arthropods:

No data available (Substances/Ingredient)

Effects on soil microorganisms:

No data available (Substances/Ingredient)

Behaviour in waste water treatment plants:

Due to its low solubility in water the product is almost completely mechanically separated in biological sewage plants.

Observe local regulations concerning effluent treatment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64742-49-0	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	Acute fish toxicity	LC50 > 10 - < 30 mg/l	96 h	Oncorhynchus mykiss	ECHA	OECD 203
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 > 22 - < 46 mg/l	48 h	Daphnia magna	ECHA	OECD 202
	Fish toxicity	NOEC 0,182 mg/l	28 d	Oncorhynchus mykiss	ECHA	
	Algae toxicity	NOEC < 1 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Crustacea toxicity	NOEC 0,317 mg/l	21 d	Daphnia magna	ECHA	
	Acute bacteria toxicity	(EC50 1065 mg/l)		Tetrahymena pyriformis	ECHA	[48h]
64742-95-6	hydrocarbons, C9, aromatics					
	Acute fish toxicity	LC50 9,2 mg/l	96 h	Oncorhynchus mykiss	ECHA	OECD 203
	Acute algae toxicity	ErC50 2,9 mg/l	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 3,2 mg/l	48 h	Daphnia magna	ECHA	OECD 202
	Fish toxicity	NOEC 1,228 mg/l	28 d	Oncorhynchus mykiss	ECHA	
	Algae toxicity	NOEC 0,22 mg/l	3 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Crustacea toxicity	NOEC 2,144 mg/l	21 d	Daphnia magna	ECHA	
	Acute bacteria toxicity	(EC50 > 99 mg/l)	0,5 h	Activated sludge	ECHA	OECD 209 [10 min]

12.2. Persistence and degradability

Abiotic degradation:

Physicochemical elimination:

Oxidation:

not applicable (Mixtures)

In air a rapid reduction is expected.

The information about ecology refers to the main components.

Hydrolysis:

not applicable (Mixtures)



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 19 of 27

It is not expected to conversion due to hydrolysis to any significant extent.

The information about ecology refers to the main components.

Photochemical elimination:

Photolysis:

not applicable (Mixtures)

It is not expected to conversion due to photolysis to any significant extent.

The information about ecology refers to the main components.

Ozonolysis:

not applicable (Mixtures)

Biodegradation:

not relevant (Mixtures)

CAS No	Chemical name	Method	Value	d	Source
		Evaluation			
64742-49-0	hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	OECD 301 F	89 %	28	ECHA	
	readily biodegradable				
64742-95-6	hydrocarbons, C9, aromatics				
	OECD 301 F	78 %	28	ECHA	
	readily biodegradable				

12.3. Bioaccumulative potential

not applicable (Mixtures)

12.4. Mobility in soil

Surface tension:

See under section 9.1 - Information on basic physical and chemical properties.

Distribution:

Water-air (volatility rate, Henry-constant):

not applicable (Mixtures)

The product is insoluble and floats on water.

Product is easily volatile.

The information about ecology refers to the main components.

Soil-Water (Adsorption coefficient):

not applicable (Mixtures)

If product enters soil, it will be mobile and may contaminate groundwater.

The information about ecology refers to the main components.

Soil-Air (volatility rate):

not applicable (Mixtures)

Product is easily volatile.

The information about ecology refers to the main components.

This product contains one or more hydrocarbon UVCB's. Standard tests for this endpoint are intended for single substances and are not appropriate for this complex substance.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

Ozone depletion potential (ODP):

No data available (Substances/Ingredient)

Photochemical ozone creation potential (POCP):

No data available (Substances/Ingredient)

Global warming potential (GWP):



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 20 of 27

No data available (Substances/Ingredient)

AOX: Product does not contain any organic halogens.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Waste treatment options (Recovery operations / Disposal operations):

Send to a hazardous waste incinerator facility under observation of official regulations.

Dispose of waste according to applicable legislation.

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Properties of waste which render it hazardous:

Flammable [HP 3]

Specific Target Organ Toxicity (STOT)/Aspiration Toxicity [HP 5]

Ecotoxic [HP 14]

Evidence for disposal must be provided.

Consult the appropriate local waste disposal expert about waste disposal.

Waste for recycling is to be classified and labelled.

For recycling, contact recycling exchanges.

May not be disposed or deposited together with domestic garbage.

Do not mix with other wastes.

Do not flush into surface water or sanitary sewer system.

Do not dispose of waste into sewer.

Before discharge in public drains (e.g. residues of washing- and rinsing liquids) please observe the relevant regulations. In case of further questions please contact your waste- or environmental representative or the responsible authority.

Clean IBCs or drums at approved facility only.

The waste producer is responsible for correct coding and designation of his wastes.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

The waste code has to be identified in agreement with the disposal company or the competent authority.

List of proposed waste codes/waste designations in accordance with EWC:

List of Wastes Code - residues/unused products

070604 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - used product

070604 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease, soaps, detergents, disinfectants and cosmetics; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Other disposal recommendations:

Contaminated packages must be completely emptied and can be re-used following proper cleaning.

Cleaning by recycling company.

Recommended cleansing agent:

Clean with detergents. Avoid solvent cleaners.

Handle contaminated packages in the same way as the substance itself.

Non-contaminated packages may be recycled.

Packing which cannot be properly cleaned must be disposed of.

As well uncleaned (empty) containers remain contaminated by product residues and may be hazardous by vapours.

Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 21 of 27

They have to be disposed by specialists or have to be supplied to a licensed reconditioning.
The conditions of the regional reconditioning companies have to be observed.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN1268
14.2. UN proper shipping name:	PETROLEUM PRODUCTS, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Classification code:	F1
Special Provisions:	664
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

Other applicable information (land transport)

Provision(s), multilateral agreement(s): Not applicable

Maximum permissible total quantity per unit of carriage according to subsection 1.1.3.6 ADR/RID: 1000 L.
Factor out of category of carriage (= 3) to calculate the quantity per unit of carriage: 1.

Inland waterways transport (ADN)

Other applicable information (inland waterways transport)

Not classified for this transport carrier.

Marine transport (IMDG)

14.1. UN number or ID number:	UN1268
14.2. UN proper shipping name:	PETROLEUM PRODUCTS, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Marine pollutant:	--
Special Provisions:	223, 955
Limited quantity:	5 L
Excepted quantity:	E1
EmS:	F-E, S-E
Segregation group:	IMDG-Code segregation group not applicable

Other applicable information (marine transport)

Exception(s): Not applicable

Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 22 of 27

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN1268
14.2. UN proper shipping name:	PETROLEUM PRODUCTS, N.O.S.
14.3. Transport hazard class(es):	3
14.4. Packing group:	III
Hazard label:	3



Special Provisions:	A3	
Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

Other applicable information (air transport)

ERG Kodex: 3L

The state variations in chapter 2.8.1 and the operator variations in chapter 2.8.3 for shipping of dangerous goods in limited quantities according to chapter 2.7 of the valid ICAO/IATA Dangerous Goods Regulations have to be observed.

The rulings for dangerous goods by air mail according to chapter 2.4 of the valid ICAO/IATA Dangerous Goods Regulations and the conventions of the Universal Postal Union (UPU) as well as the clauses of the relevant National Postal Administration have to be observed. Airmail: prohibited.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Further information see under section 6, 7, 8.

14.7. Maritime transport in bulk according to IMO instruments

No bulk transport in accordance with IBC code.

It is sold exclusively in traffic legally authorized and appropriate packaging.

Other applicable information

Postal, express and courier services:

Postal service (national):

Express freight / special delivery:

Refer to your National Postal Administration.

Courier service (national):

The general conditions of business of the particular courier service have to be observed.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 80 % (640 g/l)

Additional information

Authorisations and/or restrictions on use:

Authorisations:

Authorisation of Chemicals (REACH) as regards Annex XIV:

not relevant

Restrictions on use:

Restriction of chemicals (REACH) as regards annex XVII:

No. 3 - Liquid substances or mixtures in decoration objects to create light or color effects or jokes



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 23 of 27

- No. 40 - Substances in aerosol dispensers for entertainment and decorative purposes for supply to the general public
- No. 75 - Substances in mixtures for use in tattooing

Informations on Regulation (EC) No. 1272/2008 - Annex VI, Part 1:

Note P is valid: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.

Other regulations (EU):

Regulation (EC) No. 1005/2009 - Substances that deplete the ozone layer:

not relevant

Regulation (EC) No. 648/2004 and No 907/2006 - Detergents:

not relevant

Regulation (EC) No. 649/2012 - Export and import of dangerous chemicals:

not relevant

Regulation (EU) 2019/1021 - Persistent organic pollutants:

not relevant

Regulation (EC) No. 428/2009 and No. 388/2012 and No. 1382/2014 - Control of exports, or transfer, brokering and transit of dual-use goods (Dual-Use Regulation):

not relevant

Regulation (EC) No. 273/2004 - Drug precursors:

not relevant

Regulation (EC) No. 111/2005 - Definition of rules for the monitoring of trade in drug precursors between the Union and third countries:

not relevant

Regulation (EU) 2019/1148 - Marketing and use of precursors for explosives:

Annex I - Restricted explosives precursors:

not relevant

Annex II - Notification requirements for explosives precursors:

not relevant

Directive 2012/18/EC - Control of major accident hazards involving dangerous substances (Seveso III):

ANNEX I, PART 1 (Categories of dangerous substances):

P5c (PHYSICAL HAZARDS) - FLAMMABLE LIQUIDS, Flammable liquids, Categories 2 or 3 not covered by P5a and P5b (Column 1)

Quantities: > 5.000.000 kg (Column 2) /> 50.000.000 kg (Column 3)

ANNEX I, PART 2 (Named dangerous substances):

34. Petroleum products and alternative fuels: (a) gasolines and naphthas (Column 1)

Quantities: > 2.500.000 kg (Column 2) /> 25.000.000 kg (Column 3)

Directive 2004/42/EC - Use of organic solvents in certain paints and lacquers:

not relevant

Directive 2010/75/EU - Industrial Emissions Directive (Directive IE) - succession to Directive 1999/13/EC - Limitation of emissions of volatile organic compounds (VOC-Directive):

When using this substance / mixture it has to be checked whether the activities are subject to the the requirements of IE-RL, Chapter V (installations and activities with the use of organic solvents - VOC).

Aerosol Directive (75/324/):

not relevant

Biocide directive (98/8/EC):

not relevant

Regulation (EU) No. 528/2012 on biocides:

not relevant

Observe in addition any national regulations!

EC-Chemical inventories: All ingredients are listed in EINECS / ELINCS or excepted from listing.

National regulatory information



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 24 of 27

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Additional information

Other regulations, restrictions and prohibition regulations:

European product inventories (Registration status on mixtures):

Kemikalieinspektionen / Produktregistret / Swedish Chemicals Inspectorate - Keml (<http://www.kemi.se>):

This product was registered.

Schweizerische Eidgenossenschaft - Bundesamt für Gesundheit - BAG (<http://www.bag.admin.ch>) / Anmeldestelle

Chemikalien (<http://www.cheminfo.ch>) / Informationssystem für gefährliche und umweltrelevante Stoffe - IGS

(<http://igs.naz.ch/index.html>):

This product was registered.

International chemical inventories (Registration status on substances): No data available

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

hydrocarbons, C9, aromatics

SECTION 16: Other information

Changes

This version replaces all former issues.

Changes made in this revision see section: 2, 4, 6, 7, 8, 9, 11, 12, 13, 14, 15, 16.

Abbreviations and acronyms

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate.

CAS: Chemical Abstracts Service.

CEN: Comité Européen de Normalisation (European Committee for Standardisation).

CLP: Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.

CSA: Chemical Safety Assessment.

CSR: Chemical Safety Report.

C&L: Classification & Labeling.

DNEL: Derived No-Effect Level.

EAK: European Waste Catalogue (replaced by LoW – see below).

EC50: Effective concentration, 50 percent.

ECHA: European Chemicals Agency.

EC: European community.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances.

EN: European standard.

EWC: European Economic Community.

EEA: European Economic Area (EU + Iceland, Liechtenstein and Norway).

EU: European Union.

GHS: Globally Harmonized System of Classification and Labelling of Chemicals.



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 25 of 27

HSPA: Hydrocarbon Solvents Producers Association.
IATA-DGR: International Air Transport Association Dangerous Goods Regulations.
IBC-Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (International Bulk Chemical Code).
IC50 / ErC50: Inhibitory concentration, 50 percent.
ICAO-TI: International Civil Aviation Organization Technical Instruction.
IMDG: International Maritime Dangerous Goods.
ISO: A standard of International Standards Organisation.
IUPAC: International Union for Pure and Applied Chemistry.
LC50: Lethal concentration, 50 percent.
LD50: Lethal Dose, 50 percent.
log Kow (Pow): octanol-water partition coefficient.
LoW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>).
LQ: Limited Quantities.
MARPOL: Maritime Pollution Convention (Convention for the Prevention of Pollution from Ships).
OC: Operational Conditions.
OECD: Organisation for Economic Co-operation and Development.
OSHA: Occupational Safety and Health Agency.
PBT: Persistent, bioaccumulabe and toxic.
PEC: Predicted Effect Concentration.
PNEC: Predicted No-Effect Concentration.
PPE: Personal Protection Equipment.
(Q)SAR: Quantitative-Structure-Activity-Relationship.
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals; Regulation (EC) No 1907/2006.
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.
RMM: Risk Management Measure.
SVHC: Substances of Very High Concern.
STOT - RE: Specific Target Organ Toxicity - Repeated Exposure.
STOT - SE: Specific Target Organ Toxicity - Single Exposure.
UN: United Nations.
UVCB: Substances of Unknown or Variable composition, Complex reaction products or Biological materials.
vPvB: Very persistent and very bioaccumulable.
WoE: Weight of Evidence.

For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Key literature references and sources for data



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 26 of 27

The classification corresponds to current EC-lists, but is completed by statements of technical literature and company data.

Other public accessible sources:

Regulation (EC) No. 1907/2006 (REACH) in the valid version in each case

Regulation (EC) No. 1272/2008 (CLP) in the valid version in each case

Further information and practical guides on the internet:

European Chemicals Agency - ECHA (<http://echa.europa.eu>)

ECHA - Information on Chemicals (<http://echa.europa.eu/information-on-chemicals>)

ECHA - Candidate List of Substances of Very High Concern for Authorisation

(<http://echa.europa.eu/de/candidate-list-table>)

ECHA - List of restrictions table

(<http://echa.europa.eu/de/addressing-chemicals-of-concern/restrictions/list-of-restrictions/list-of-restrictions-table>)

ECHA - Authorisation List

(<http://echa.europa.eu/hr/addressing-chemicals-of-concern/authorisation/recommendation-for-inclusion-in-the-authorisation-list/authorisation-list>)

ECHA - C&L Inventory (<http://echa.europa.eu/en/web/guest/regulations/clp/cl-inventory>)

eChemPortal (<http://www.echemportal.org>)

The access to European Union law - EUR-Lex (<http://eur-lex.europa.eu>)

Health and Safety Executive (<http://www.hse.gov.uk>) / Control of Substances Hazardous to Health Regulations - COSHH

(<http://www.coshh-essentials.org.uk/Home.asp>)

Pollution Prevention and Control Act and Pollution Prevention and Control Regulations

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

Full text of all R-, H-, EUH-phrases which are referred to in section 2 and 3 of this safety data sheet - see previous list.

These (this) R-, H-, EUH-phrases/R-, H-, EUH-phrase apply/applies to the substance(s) of content, however, it does not necessarily show the classification of the product.

Recommended restriction of application:

See under section 1.2 - Uses advised against.

Use this product only for intended purpose in accordance with our product informations.

Please refer to our internet website for more information (<http://www.acmos.com>).

Training advice:

Yearly briefing and instruction of employees by means of operating instructions according to article 8 of EC-directive 98/24/EC.

Inquiry office: Laboratory (Division: Occupational- /Product security)

Contact person: Mr. Dryhaus (Telephone: +49-421-5189-0, Telefax: +49-421-5189-871)

Office hours: Mo - Th from 7.30 - 16.15 h and Fr from 7.30 - 13.30 h. Out of office hours no call diversion.

Disclaimer:

The information is based on the present level of our knowledge. It does not, however, give assurance of product



Safety Data Sheet

Information following the respective legal area

WAXILIT 22-71F

Revision date: 21.03.2023

Page 27 of 27

properties and establishes no contract legal rights. The information contained herein are, to our knowledge at the time of their creation to be correct and been taken from sources deemed to be reliable. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. The receiver of our product is singularly responsible for adhering to existing laws and regulations. All descriptions are approximate values, they are not specified for construction of specifications. This safety data sheet does not represent any operating instruction according to national chemical regulations. It may be used for creation, but must not replace it. The employer is not relieved from his duties. All technical information to occupational protection are directed predominately to experts first (safety engineers, occupational medicines).